




FIG. 2










FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15

FIG. 16




FIG. 17




FIG. 18





FIG. 19






FIG. 21



FIG. 22 PRIOR ART





FIG. 23






FIG. 25




FIG. 26




FIG. 28




FIG. 29




FIG. 30





FIG. 31



## Phoenix Network Health Monitor Interface

Visibility into the network is a primary concern of the Vortex team.

It is the job of the network management architecture to enable this visibility. Without it, the network cannot be effectively run: faults cannot be located and corrected, capacity planning cannot be done, and progressive problems cannot be found and stopped from reaching a critical stage until it is too late.

The architecture is generally divided up into three parts: collectors (also known as 'probes'), data warehouses, and reporting tools. Collectors include devices such as the NetScout RMON probe and two in-house warehouses consist of Oracle databases residing on Market and National Vertex Servers. These databases run on Sun Microsystems UNIX workstations that have RAID mass storage systems built in. The reporting tools are primarily the web-based tools hosted by the Market VERTEX Servers.

Follow the links along the left-hand side of the page to gain access to VERTEX reports.

Until a permanent home is picked, hasd size graphs can be found here.



FIG. 32

## User/Channel Distribution by Sector

Enter Query Date in YYYYMMDD format: 20001215 Draws


Active Modem Percentage: modem counts in polling, contention, and dedicated over total WBRs.

All sectors between 2000-12-15 00:01:20 and 2000-12-15 16:22:41 GMT


-sb203-32
-sb204-32
-sm 001
-sm 063
-sm 102-32
-sm 102-32
-sm 103-32
-sm 103-32
-sm 103-32
-sm 104-32
-sm 103-32
-sm 1


## Sector sb203-32 on hm01.phoenix.speedchoice.com

Click on the summary for detailed graphs.



[FEC Summary] [FEC Channel] [SNR Summary] [Peak Load/Capacity: 103 %]











FIG. 34










FIG. 35

## Signal to Noise graph for sb203-32





FIG. 36

# Load and Capacity



Remote HSMP Query Form					
Access Level	BWG Engineer				
IP Address e.g, 24.221.13.83	Note: Enter an IP address -OI- a User ID; not both				
User ID e.g, 149219	Note: This corresponds to the UUID field in the database				
Query Type	O Custom query:  Note: Only administrators can perform custom queries				
Submit-Request(s)					
Warning: This could	take up to 30 seconds per query; please be patient				

FIG. 38

# Hybrid Probe - Phoenix

Start time: 00:00:00	End time: 18:22:19
Start date: 12.19.00	End date: 12.19.00

Number of entries: 10

CSV Format

Get Results

Start time: 12-19-00 00:00:00 GMT

End time: 12-19-00 18:22:19 GMT

Currently: 12-19-00 18:22:24 GMT

IP Address | Active - % Ratio | Poll - Timer | Ded - Timer | Poll - Tx bytes | Ratio | Ded - Tx bytes | Ratio | Index | Ratio N/A N/A N/A N/A N/A N/A N/A N/A 0:0:0:0:0 0:0:0:0:1 |N/A | 0:0:0:0:0 |N/A | 0:0:0:0:1 Total (all) N/A Average (all) N/A

FIG. 39

## **Top Talkers**

Total Users = 812

Total number of upstream bytes for all users = 12983.77 MB's Total number of downstream bytes for all users = 116697.0 MB's

Average number of upstream bytes per user = 15.99 MB's Average number of downstream bytes per user = 143.72 MB's

Date Range Searched: From to 2000-12-11 23:59:59

CMID	Up MegaBytes	% of Total	Information	CMID	Down MegaBytes	% of Total	Information
10000002309	1078.07	8.30	Info Detail	10000000462	4544.09	3.89	Info Detail
1000015561	572.24	4.41	Info Detail	10000020500	3811.87	3.27	Info Detail
1000007207	385.66	2.97	Info Detail	10000000698	3701.56	3.17	Info Detail
10000017759	357.82	2.76	Info Detail	10000006338	3395.66	2.91	Info Detail
10000014703	347.42	2.68	<u>Info</u> <u>Detail</u>	10000005958	3342.65	2.86	Info Detail
10000000555	308.35	2.37	Info Detail	10000002126	3272.81	2.80	Info Detail
10000012777	217.74	1.68	Info Detail	10000001712	2838.66	2.43	<u>Info</u> <u>Detail</u>
10000021854	195.93	1.51	Info Detail	10000001410	2618.56	2.24	<u>Info</u> <u>Detail</u>
1000028475	195.15	1.50	Info Detail	10000013661	2540.65	2.18	Info Detail
10000002871	180.43	1.39	Info Detail	10000006955	2505.09	2.15	Info Detail
10000009310	174.94	1.35	<u>Info</u> <u>Detail</u>	10000010571	2246.71	1.93	Info Detail

# Detail Information for CMID 10000002309

#### Breakdown By Protocol

Protocol	Upstream Bytes	% of Total	Downstream Bytes	% of Total
HTTPS	437990	0	3649130	0
IP	1077630687	99	1089385948	99
Totals	1078068677		1093035078	

## Breakdown By IP Address

IP Address	Upstream Bytes	% of Total	Downstream Bytes	% of Total
24.221.206.66	1077630687	99	1089385948	99
24.221.206.71	437990	0	3649130	0
Totals	1078068677		1093035078	

Protocol	Upstream Bytes	% of Total	Downstream Bytes	% of Total
IP	1077630687	100	1089385948	100
Totals	1077630687		1089385948	

FIG. 41

#### Statistics for Market ID 00000010, Market name = Phoenix (new)

Market ID	Date	HR	# of Subscribers	Mb Per Hour	Avg Per Subscriber	Avg MBPS	Peak#of MBPS
00000010	2000-12-12	00	000003	000000054.53	001817.00	000000.01	000000026.01
00000010	2000-12-12	01	000003	000000158.73	005291.00	000000.04	000000118.64
00000010	2000-12-12	02	000002	000000187.85	009392.00	000000.05	000000102.37
00000010	2000-12-12	08	000001	000000055.31	005531.00	000000.01	000000055.31
00000010	2000-12-12	10	000004	000000140.21	003505.00	000000.03	000000084.61
00000010	2000-12-12	11	000001	000000008.07	000807.00	00.00000	000000008.07
00000010	2000-12-12	12	000004	000000024.41	000610.00	00.00000	000000013.55
00000010	2000-12-12	13	000001	000000002.41	000241.00	00.00000	000000002.41
00000010	2000-12-12	15	000001	000000008.83	000883.00	00.0000.00	000000008.83
00000010	2000-12-12	17	000001	000000001.28	000128.00	00.00000	000000001.28
00000010	2000-12-12	19	000001	000000025.82	002582.00	00.00000	000000025.82
00000010	2000-12-12	20	000001	000000024.97	002497.00	00.00000	000000024.97
00000010	2000-12-12	21	000001	000000023.37	002337.00	000000.00	000000023.37

Statistics for udfg id 526, udfg name = south mtn 101-32/36

Total subscribers in SIF: 110

<u> </u>						
nqtå in	Date	HR	Active Subscribers	MegaBits Per Hour	Avg Per Subscriber Per Second	Peak # of MBPS
526	2000-12-11	00	3	34.30	19.10	27.21
526	2000-12-11	01	5	541.81	180.181	388.12
526	2000-12-11	02	2	128.5	10.85	73.6
526	2000-12-11	03	5	761.39	253.239	731.53
526	2000-12-11	04	2	6.14	5.14	5.75
526	2000-12-11	05	5	442.1	14.221	403.91
526	2000-12-11	06	4	266.43	111.3	159.45
526	2000-12-11	07	2	2.99	2.59	1.94
526	2000-12-11	08	2	486.33	405.33	363.5
526	2000-12-11		4	312.11	130.11	221.18
526	2000-12-11	!===	3	1111.96	617.136	797.57
526	2000-12-11	11	3	49.74	27.114	27.77
526	2000-12-11	:===	4	50.63	21.23	41.30
526	2000-12-11		3	281.76	156.96	204.44
526	2000-12-11		4	598.4	16.224	319.80
526	2000-12-11		3	778.66	432.106	525.49
526	2000-12-1	<u> </u>	-	12.77	7.17	11.60
526	2000-12-1	⊰==		27.20	22.80	26.46
526	2000-12-1		<u> </u>	14.80	4.280	6.12
526	2000-12-1	<b>≒</b> ==		1.90	3.10	1.90
526	2000-12-1	⇉≔		44.86	14.286	35.99

# rotoco his is ali

#### Detail for IP nnn nnn nnn nnn from to 2000-12-12 23:59:59

This is a protocol breakdown for traffic from this IP address. This includes all protocol types, including all TCP and UDP protocols. Two special protocols, TCP~ and UDP~, correspond to "unknown TCP protocol" and "unknown UDP protocol". This means that we don't really know what kind of traffic it is at this point.

Protocol Downstream KBytes Upstream KBytes

Totals:

Up: Kbytes Down: Kbytes

# Protocol Summary - 2000-12-12 00:00:00 to 2000-12-12 23:59:59


This is alist of the most popular protocols on our network for the chosen date range. Measurements are in Megabytes and the da range is inclusive. Again, TCP~ and UDP~ represent "other" TCP and UDP apps which have not yet been identified.

Protocol Name	Megabytes Transferred
NNTP	60997.67
TCP~	20632.16
NAPSTER	10798.85
FTP-DATA	8756.72
HTTP	6938.55
UDP~	3909.48
HTTPS	1215.48
POP3	571.60
AOL	183.04
FTP-CTRL	12.31
REALAUD	10.20
TELNET	8.48
SOCKET	6.92
SQLNET_N	4.31
SUNRPC_T	0.10
COMPUSRY	0.04

## Router Traffic Analysis

Daily Graph (5 Minute Average)

FastEthernet5/0/0



# Traffic Analysis for FastEthernet5/0/0 edge01.phoenix.speedchoice.com

System:

edge01.phoenix.speedchoice.com in

Maintainer:

Description: FastEthernet5/0/0 ifType: ethernetCsmacd (6)

ifName: Fa5/

Fa5/0/0

Max Speed: 12.5 MBytes/s


207.240.93.202 (edge01)

Ip:


The statistics were last updated Friday, 15 December 2000 at 21:00,


The statistics were last updated Friday, 15 December 2000 at 21:00, at which time 'edge01.phoenix.speedchoice.com' had been up for 84 days, 10:51:32.

#### Daily' Graph (5 Minute Average)



Max In:8409.8 kB/s (67.3%) Average In:5645.1 kB/s (45.2%) Current In:6166.0 kB/s (49.3%) Max Out:1446.9 kB/s (11.6%) Average Out: 944.8 kB/s (7.6%) Current Out: 1017.5 kB/s (8.1%)










FIG. 45








FIG. 46

	Peak T	Cime: 2000-12-28 12:25:00	CST	
Peak Active Modems	Sampled Modems			Activity Ratio
905		7115		12.72%
	Contention 0	Modem Counts Polling 847	Dedicated 58	
	Off Peak	Time: 2000-12-28 06:00:	00 CST	
Off Peak Active Modems		Sampled Modems		Activity Ratio
152		7115		2.14%
	Contention 0	Modem Counts Polling 98	Dedicated 54	•
		Individual Peak Modem Counts		
Contention 2000-12-28 12:55:00 CS	Т	Polling 2000-12-28 12:25:00 CST	26	Dedicated 000-12-28 05:45:00 CST
· 10		847		88
		Avg. Time Spent Per User		
In Contention		In Polling		In Dedicated
0.03 secs		0.71 secs		1.48 secs

FTP Rates At Off Peak 2000-12-28 06:00:00 CST FTP Rates At Peak 2000-12-28 12:25:00 CST

Downstream	Upstream	Downstream	Upstream
3.54 Mbps	85.83 Kbps	2.21 Mbps	32.02 Kbps

#### 2000-12-28 00:00:00 CST thru 2000-12-28 23:59:59 CST

Average FTP Rate Midnight-6pm (off peak)

Average FTP Rate 6pm-Midnight (peak)

Downstream 2.69 Mbps

Upstream 51.31 Kbps Downstream 2.01 Mbps

Upstream 38.27 Kbps

#### 2000-12-28 00:00:00 CST thru 2000-12-28 23:59:59 CST

Average HTTP Rate Midnight-6pm (off peak) 470.34 Kbps

Average HTTP Rate 6pm-Midnight (peak) 384.46 Kbps

FEC Corrections 32.55:1000

FEC Uncorrectables 1.53 %

Available Channels

230

Max Functioning Channels

Min Functioning Channels

Avg Functioning Channels

230

68

226.44

Max Non-Functioning Channels

Min Non-Functioning Channels

Avg Non-Functioning Channels

162

0

3.56

Signal to Noise Ratio

24.93:1

Requested to Scheduled · Modem Calibration Ratio

0.65:1

#### Downstream to Upstream Bitrate Ratio (All MEASUREMENTS ARE PER USER)


12-28

4.01:1

4.46:1

10.68:1

4.56:1



Bits ber second

FIG. 48